

KHEV 8-45 BL (600766620) 1 3/4" Combination Hammer Plastic Carry Case

Order no. 600766620
EAN 4061792002623



Representative picture



- Maximum drilling progress and good demolition performance thanks to brushless motor and high-performance hammer action
- Long service life thanks to brushless technology and robust cast aluminum housing for drive unit and motor
- Combination hammer with 2 functions: hammer drilling, drilling, and chiseling
- Metabo VibraTech (MVT) with double damping: decoupled handle and impact-absorbing oscillating weight reduce active vibrations for safe work, even with long-term use.
- Ergonomically shaped, slim handle with large speed control trigger for comfortable work
- Easy to reach locking switch for chiseling in continuous mode
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Optional speed and impact energy reduction for working on softer materials
- Electronic soft start for precise spot-drilling
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- Restart protection: prevents unintentional start-up after power supply interruption
- Overload protection: protects the motor from overheating
- Low-dust chiseling and drilling with external ESA max dust extraction (accessories)

Technical values

Parameters

| | |
|--|---------------|
| Max. single blow energy (EPTA) | 12.2 J |
| Amps | 14.8 AMPS |
| Maximum impact rate | 2900 BPM |
| Rated input power | 1500 W |
| Max. capacity in concrete with hammer drills | 1 3/4 " |
| Max. capacity in masonry with core bits | 4 15/16 " |
| No-load speed | 210 / 300 RPM |
| Speed at rated load | 210 / 300 RPM |
| Bit retainer | SDS-max |
| Collar diameter | 3 5/32 " |
| Weight (without power cable) | 22.3 lbs |
| Cable length | 236 7/32 ft |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 12.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 10.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- rubber-coated handle
- Lubricant for tool shank end
- Duster
- Plastic carrying case