

## 650 W Socket welder

For quick and easy fusion of PP, PB, PE & PVDF plastic pipes and fittings


Art.-No. 036051 / EAN 4004625360514

### Contents

- 4 mandrels and sockets with non-stick coating (20mm, 25mm, 32mm, 40mm)
- 1 Tough metal carry case
- 1 Stable table stand
- 1 Fixing bolt
- 1 Allen key
- Heating element with non-stick coating
- VDE approved site quality mains cable H05RN-F 3G 0.75 mm

### Performance:

- Working temperature 260°C
- With thermostatic control



## 800 W Socket welder

For quick and easy fusion of PP, PB, PE & PVDF plastic pipes and fittings

Art.-No. 036052 / EAN 4004625360521

### Contents

- 6 mandrels and sockets with non-stick coating (20mm, 25mm, 32mm, 40mm, 50mm, 63mm)
- 1 Tough metal carry case
- 1 Stable table stand
- 1 Fixing bolt
- 1 Allen key
- 1 Table vice for horizontal and vertical use
- Heating element with non-stick coating
- VDE approved site quality mains cable H07RN-F 3G 1,50 mm

### Performance:

- Working temperature 260°C
- With thermostatic control



## 800 W Socket welder

For quick and easy fusion of PP, PB, PE & PVDF plastic pipes and fittings

Art.-No. 036062 / EAN 4004625360620

### Contents

- Digital display
- 6 mandrels and sockets with non-stick coating (20mm, 25mm, 32mm, 40mm, 50mm, 63mm)
- 1 Tough metal carry case
- 1 Stable table stand
- 1 Fixing bolt
- 1 Allen key
- 1 Table vice for horizontal and vertical use
- Heating element with non-stick coating
- VDE approved site quality mains cable H07RN-F 3G 1,50 mm

### Performance:

- Working temperature 200- 279°C
- Electronically regulated



## 1300 W Socket welder

For quick and easy fusion of PP, PB, PE & PVDF plastic pipes and fittings

Art.-No. 036063 / EAN 4004625360637

### Contents

- Digital display
- 3 mandrels and sockets with non-stick coating (75mm, 90mm, 110mm)
- 1 Tough metal carry case
- 1 Stable table stand
- 1 Fixing bolt
- 1 Allen key
- 1 Table vice for horizontal and vertical use
- Heating element with non-stick coating
- VDE approved site quality mains cable H07RN-F 3G 1,50 mm

### Performance:

- Working temperature 200- 279°C
- Electronically regulated