

# DCX-250 XPERT

Suitable for intensive cutting of porcelain, stoneware and ceramic tile.  
For occasional cutting of natural stone such as marble or granite.



2 cv/hp



3 9/16" / 90 mm



PATENTED



**1** Reinforced aluminium chassis with innovative triple beam system and steel sides. Improves the stability and rigidity of the chassis.

**2** Reinforced cutting guide for a better cut finish.

**3** New adjustable cooling system. Increases cooling efficiency and reduces water dispersion.

**4** High performance plunge effect. Cutting height adjustment.

- Includes transport handle and off-road type reinforced wheels, which provide better transportability and handling of the machine.
- Steel double settling system for improved efficiency and water recovery.
- Angular measurement with aluminium square adjustable from 0° to 60° for repetitive cuts.
- Includes reinforced folding legs with folding-prevention system and quick lock.
- External and easy to remove water tank with 30 L capacity.
- Includes improved splash guard system with auto-sliding protective cover.
- Patented ZERO DUST system exclusive to RUBI certified by the TNO, for safe exposure thanks to the reduction of the breathable dust particles generated during the cut.
- Ergonomic bi-material handle for comfortable operation of the cutting head.
- Earth integrated into the chassis.
- Does not include power cable.
- Not Supplied with a blade.

### Accessories:



Ref. 51927

Set of Flanges Ø170mm DCX-250

DCX-250 XPERT 1250	PREMIUM	52 3/8" 133 cm	49 3/16" 125 cm	35 7/16x35 7/16" 90x90 cm	2 3/8 / 3 9/16" 60 / 90 mm	115/16" 50 mm	1" 25.4 mm	10" 250 mm	172 Lb 78 kg	1	**1	
DCX-250 XPERT 1550	PREMIUM	64 3/16" 163 cm	61 1/16" 155 cm	43 5/16x43 5/16" 110x110 cm	2 3/8 / 3 9/16" 60 / 90 mm	115/16" 50 mm	1" 25.4 mm	10" 250 mm	190 Lb 86 kg	1	**1	

The cutting capacities can vary depending on the head position, special flanges and disc diameter.

	REF	52960	52961	52962
DCX-250 XPERT 1250	<b>Voltage</b>	230V-50Hz.	110V-50Hz.	120V-60Hz.
	<b>RPM</b>	2750	2750	3350
DCX-250 XPERT 1550	<b>REF</b>	<b>52970</b>	<b>52971</b>	<b>52972</b>
	<b>Voltage</b>	230V-50Hz.	110V-50Hz.	120V-60Hz.
	<b>RPM</b>	2750	2750	3350